


Aurelia FE 4030

Innovative, newly formulated Trunk Piston Engine Oil delivering fuel economy savings.



APPLICATIONS

Lubrication of four stroke medium speed engines in marine and power generation applications using high sulfur residual fuels.

Engines using residual heavy fuel oil with high sulfur content

FEATURES AND BENEFITS

Aurelia FE 4030 is a uniquely formulated lubricant typically delivering 1.5% reduction in fuel consumption when compared to equivalent conventional products*.

Aurelia FE 4030 combines an exclusive formulation of the latest additive technologies, developed by the TotalEnergies Research Center.

The product utilizes highly refined base oils to provide a substantial safety margin able to cope with higher stress levels.

**Weighted average of measured fuel savings at different engine loads, according to E3 engine cycle as defined in MARPOL. Fuel savings obtained by use of Aurelia FE vs Aurelia TI. Methodology certified by Bureau Veritas.*

SPECIFICATIONS AND APPROVALS

✓	MaK		

TECHNICAL DATA : Aurelia FE 4030

CHARACTERISTICS	METHODS	UNITS	TYPICAL VALUES*
S.A.E. Grade	—	—	40
Density at 15°C	ASTM D4052	kg/m ³	877
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s	82.5
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	13.5
Flash Point (COC)	ASTM D92	°C	≥ 220
Pour Point	ASTM D97	°C	≤ -12
TBN	ASTM D2896	mgKOH/g	30

*The specifications above are for illustrative purposes and communicated for information only.

CUSTOMER BENEFITS

✓	Proven Fuel Economy of 1.5%* measured on a bench test engine following MARPOL IV E3 load cycle, methodology validated by Bureau Veritas.
✓	Superior engine protection and cleanliness.
✓	Exceptional thermal stability and detergency, preventing varnish formation.
✓	Minimal deposit formation ensured by excellent cleanliness of hot engine components.
✓	Excellent thermal resistance and oxidation resistance.
✓	Excellent anti-wear protection and corrosion resistance.

GENERAL RECOMMENDATIONS

COMPATIBILITY

Compatible with comparable engine oils. Mixing Aurelia FE with a traditional lubricant will significantly impact the fuel economy benefits.

Please consult your Lubmarine Lubrication Engineer should you have any questions.

STORAGE

This product should be stored under cover in clean, dry conditions and protected from frost.

Recommended storage temperature range is 5°C to 50°C.

Drums that are stored on deck should be raised on pallets and covered to protect from the elements.

COMPLIMENTARY PRODUCTS AND SERVICES

✓	WT Supra – Innovative and environmentally friendly cooling system inhibitor concentrate.
✓	LubDiag – Oil Analysis – Laboratory based used oil analysis program.
✓	LubInsight – Suite of onboard testing equipment.
✓	LubSkills – Lubmarine Engineers are on hand at worldwide locations to assist with lubrication concerns.
✓	Lube On Ship – Visualize your lubricants needs aboard Lubmarine's innovative virtual vessel. lubmarine.totalenergies.com/lube-on-ship